

Oven Controlled Crystal Oscillator

- Low power consumption
- Excellent temperature stabilities
- High stability overtone crystal
- Fast warm-up

CO602



Specifications:

Frequency Range:	1.0 MHz or 160.0 MHz	
Operating Temperature:	0°C ~ +50°C	- A
	-10°C ~ +45°C	- B
	-10°C ~ +55°C	- C
	-20°C ~ +60°C	- D
	-30°C ~ +70°C	- E
Storage Temperature:	-40°C ~ +85°C	
Frequency Stability:		
Accuracy:	$\pm 5 \times 10^{-9}$	
Vs. Temperature:	$\pm 5 \times 10^{-7}$	- 57
	$\pm 1 \times 10^{-7}$	- 17
	$\pm 5 \times 10^{-8}$	- 58
	$\pm 1 \times 10^{-8}$	- 18
	$\pm 5 \times 10^{-9}$	- 59
Short-Term Stability:	$\pm 1 \times 10^{-10}$	per second
Aging Rate:	$\pm 1 \times 10^{-9}$	per day
	$\pm 5 \times 10^{-8}$	per year max
Output Waveform:	Sine Wave, HCMOS	
Output Level:	2dBm min. Sine Wave TTL, HCMOS compatible	
Phase Noise (10MHz):	-120dBc/Hz	@ 10Hz
	-140dBc/Hz	@ 100Hz
	-145dBc/Hz	@ 1KHz
	-150dBc/Hz	@ 10KHz
Harmonics Distortion:	-25 dB	
Supply Voltage:	+3.3 VDC ($\pm 5\%$)	
	+5.0 VDC ($\pm 5\%$)	- P
Supply Current:	300mA max at warm-up 100mA max after warm-up at 25°C	
Frequency Adjust:	± 3.0 ppm (AT-cut), ± 1.0 ppm (SC-cut),	

Note:

1. Other frequencies, stabilities, and operating temperature ranges available. Consult VTC Support for specific requirements.
2. Not all combinations of the above, stabilities, and temperature ranges are available. Consult VTC Support if your requirement is not standard.
3. All specifications subject to change without notice.

CO-C



Pin	Configurations
1	Vcc
2	Vref
3	Vc/Nc
4	Ground
5	Output

All dimensions are in mm

Ordering Information

Product name + Temperature + Stability + Frequency + Other Specification Code.

i.e. CO602C18-10.0MHz

or CO602D58P-10.0MHz