

- **Ideal for DBS Receivers, IF Filter**
- **Constant Group Delay**
- **Improved ESD capability by integrated shunt resistors**
- **Rugged, Hermetic, Low Profile TO-39 Package**
- **Complies with Directive 2002/95/EC (RoHS Compliant)**

**SF480-6**

Absolute Maximum Rating (Ta=25°C)			
Parameter		Rating	Unit
AC Voltage Between Any Two Pins	$V_{FP}$	5	V
DC Voltage Between Any Two Pins	$V_{DC}$	0	V
Operating Temperature Range	$T_A$	-25 ~ +85	°C
Storage Temperature Range	$T_{stg}$	-40 ~ +85	°C

Electronic Characteristics of Channel 1						
Parameter		Sym	Minimum	Typical	Maximum	Unit
Center Frequency (25°C)	Between 3dB point	$f_c$	NS	480.00	NS	MHz
	Tolerance from 480.00 MHz	$\Delta f_c$	-	-	1.0	MHz
Insertion Attenuation		$\alpha$	-	21.5	23.5	dB
3dB Bandwidth		$BW_3$	-	8.0	-	MHz
Relative Attenuation	476.00 MHz	$\alpha_{rel}$	-	3.0	5.4	dB
	484.00 MHz		-	2.6	5.3	dB
	Lower Sidelobe 410.00 ... 465.00 MHz		37	45	-	dB
	Upper Sidelobe 491.50 ... 499.00 MHz		34	41	-	dB
	499.00 ... 550.00 MHz		38	47	-	dB
Reflected Wave Signal Suppression	0.19µs ... 2.0µs after main pulse	-	40.0	46.0	-	dB
Amplitude Ripple (p-p)	478.00 ... 482.00 MHz	$\Delta\alpha$	-	0.7	1.5	dB
Group Delay Ripple (p-p)	476.00 ... 484.00 MHz	$\Delta\tau$	-	13.0	18.0	ns
Temperature Coefficient of Frequency		$FTC$	-	-86	-	ppm/K

Electronic Characteristics of Channel 2						
Parameter		Sym	Minimum	Typical	Maximum	Unit
Center Frequency (25°C)	Between 3dB point	$f_c$	NS	480.00	NS	MHz
	Tolerance from 480.00 MHz	$\Delta f_c$	-	-	1.0	MHz
Insertion Attenuation		$\alpha$	-	23.5	25.5	dB
3dB Bandwidth		$BW_3$	-	54.5	-	MHz
Relative Attenuation	452.50 MHz	$\alpha_{rel}$	-	4.0	5.5	dB
	507.50 MHz		-	3.0	5.3	dB
	Lower Sidelobe 410.00 ... 440.00 MHz		37	44	-	dB
	Upper Sidelobe 518.00 ... 550.00 MHz		36	41	-	dB
	Reflected Wave Signal Suppression		0.12µs ... 2.0µs after main pulse	-	40.0	46.0
Amplitude Ripple (p-p)	461.00 ... 499.00 MHz	$\Delta\alpha$	-	0.6	1.2	dB
Group Delay Ripple (p-p)	452.50 ... 507.50 MHz	$\Delta\tau$	-	11.0	18.0	ns
Temperature Coefficient of Frequency		$FTC$	-	-86	-	ppm/K

NS = Not Specified



# 480.00 MHz SAW Filter



## Notes:

- The frequency  $f_c$  is defined as the midpoint between the 3dB frequencies.
- Unless noted otherwise, all measurements are made with the filter installed in the specified test fixture that is connected to a 50Ω test system with VSWR  $\leq 1.2:1$ . The test fixture L and C are adjusted for minimum insertion loss at the filter center frequency,  $f_c$ . Note that insertion loss, bandwidth, and passband shape are dependent on the impedance matching component values and quality.
- Unless noted otherwise, specifications apply over the entire specified operating temperature range.
- The specifications of this device are based on the test circuit shown above and subject to change or obsolescence without notice.
- All equipment designs utilizing this product must be approved by the appropriate government agency prior to manufacture or sale.
- Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.
- For questions on technology, prices and delivery please contact our sales offices or e-mail sales@vanlong.com.

## Package Dimensions (TO-39-4)



## Electrical Connections

Terminals	Connection
1	Input / Output
2	Output 2 / Switch Ground
3	Output 1 / Switch Ground
4	Case Ground

## Package Dimensions


Dimensions	Nom. (mm)	Tol. (mm)
A	9.35	$\pm 0.10$
B	3.40	$\pm 0.10$
C	3.00	$\pm 0.20$
D	0.45	$\pm 0.10$
E	5.08	$\pm 0.10$
F	2.54	$\pm 0.20$
G	1.0	
H	0.6	

## Marking



Ink Marking  
Color: Black or Blue

## Equivalent LC Model



## Typical Frequency Response

