

- **Ideal for PCN System Selectivity in 1842.50 MHz**
- **Low-Loss, High Attenuation**
- **Simple External Impedance Matching**
- **Ultra Miniature Ceramic DCC6C SMD Package**
- **Complies with Directive 2002/95/EC (RoHS Compliant)**

SF5016

Absolute Maximum Rating (Ta=25°C)			
Parameter		Rating	Unit
Input Power Level	P_{in}	10	dBm
DC Voltage VDC Between Any Two Pins	V_{DC}	5	V
Operating Temperature Range	T_A	-10 ~ +65	°C
Storage Temperature Range	T_{stg}	-40 ~ +85	°C


Electronic Characteristics						
Parameter		Sym	Minimum	Typical	Maximum	Unit
Nominal Frequency (at 25°C) (Center frequency between 3dB point)		f_c	NS	1842.50	NS	MHz
Insertion Loss	1805.0 ... 1880.0 MHz	IL	-	3.5	5.0	dB
Amplitude Ripple	1805.0 ... 1880.0 MHz	$\Delta\alpha$	-	1.8	2.5	dB
Absolute Attenuation						
	DC ... 1500.0 MHz		20	22	-	dB
	1600.0 ... 1710.0 MHz		22	25	-	dB
	1710.0 ... 1785.0 MHz	α_{rel}	10	20	-	dB
	1920.0 ... 2400.0 MHz		24	27	-	dB
	3610.0 ... 3740.0 MHz		20	25	-	dB
	5415.0 ... 5640.0 MHz		10	15	-	dB
Input / Output Impedance (nominal)		-	-	50	-	Ω

NS = Not Specified

Notes:

1. The frequency f_c is defined as the midpoint between the 3dB frequencies.
2. Unless noted otherwise, all measurements are made with the filter installed in the specified test fixture that is connected to a 50 Ω test system with VSWR \leq 1.2:1. The test fixture L and C are adjusted for minimum insertion loss at the filter center frequency, f_c . Note that insertion loss, bandwidth, and passband shape are dependent on the impedance matching component values and quality.
3. Unless noted otherwise, specifications apply over the entire specified operating temperature range.
4. The specifications of this device are based on the test circuit shown above and subject to change or obsolescence without notice.
5. All equipment designs utilizing this product must be approved by the appropriate government agency prior to manufacture or sale.
6. Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.
7. For questions on technology, prices and delivery please contact our sales offices or e-mail sales@vanlong.com.

Package Dimensions (DCC6C)




Electrical Connections

Terminals	Connection
2	Input
5	Output
1,3,4,6	Case Ground

Package Dimensions


Dimensions	Nom (mm)	Dimensions	Nom (mm)
A	1.5	E	3.0
B	0.6	F	3.0
C	1.5	G	1.1
D	1.8		

Marking



1. F5016 - Part Code
2. Date Code:
Y : Last digit of year
WW : Week No.

Test Circuit



Typical Frequency Response

